

PAI-Trex One

The True All-In-One Solution. PAI-Trex One is the industry's first, true all-in-one solution. The compact design brings together all the hardware needed for today's Check 21 standard and beyond.

ONE DEVICE

PAI-Trex One combines our proven dual-communication PAI Trex IP terminal with our dual-sided check and 2D barcode scanner in a compact footprint. This combination provides tremendous hardware and software capability in one terminal while saving valuable counter space.

ONE SPEED

PAI-Trex One is built for speed. It's blazing 32-bit ARM9 processor, enormous 64MB flash memory, high-speed scanner and industry-leading 22 line-per-second printer allows merchants to speed customers through the line. The 3.5-inch graphical touch screen color LCD allows for quick information entry at the point of sale.

ONE OBJECTIVE

PAI-Trex One, the affordable, true all-in-one solution for merchants.



POS Terminal • Check Scanner • 2D Barcode DL Scanner

PAI-Trex One



SPECIFICATIONS

Processor: 32-bit ARM9 processor
Memory: 64MB Flash, 32MB SDRAM
Real Time Clock (RTC): RTC has power back up for data retention while the external power is turned off
Magnetic Stripe Card Reader (MSR): ISO MSR will read track 1, 2, 3
SD Card Reader: Integrated
Display: 3.5-inch graphical touch screen color LCD
Keypad: Software programmable; integrated LED backlight
Speaker: Integrated Multi-tone speaker

Full Graphic Thermal Printer:

- Clamshell design
- Number of dots per line: 384 Dots
- Printing width: 48mm
- Paper width: 57mm
- Printing speed: 22+ lines per second

Communication Options:

- 2 RS232 ports
- 1 RJ45 Ethernet port
- 1 Dial up port
- Wired dial modem: 14,400bps - V.21, V.22, V.22bis, V.23, V.32, V.32bis, Bell 103 and Bell 212

Power: AC/DC power adapter, external, 100-240V

Environmental specifications:

- Operating temperature: 0°C-40°C
- Operating humidity: 10% to 90% non-condensing
- Printer operating temperature: 0°C-40°C

Scanner:

- Duplex check imager and 2D barcode reader
- Single feed check scanner
- High speed scan: 350mm/sec
- Jitter free transport mechanism for reading MICR characters
- Sensor: CIS (Contact Image Sensor)
- Scan width: 104mm
- Resolution: 200dpi
- Color: 1bit B/W
- Image formats: TIFF G4
- MICR reader recognize code: E13B
- Read head: Magnetic head with permanent magnet excitation

For more information contact Payment Alliance International
at 866.371.2273 or go to GoPAI.com.



Payment Alliance International...Payment Innovations for a Changing World

PTRX1_SS-0912